



Wellness Enterprises, LLC
418 SW 140th Terrace
Newberry, FL 32669

Toll-free: 800-428-9419
Tel: 352-333-0480
Fax: 352-333-0490

Kitchen S-III Performance Data Sheet

Note: All tests completed in accordance with NSF/ANSI standards 42 & 53 for reduction of the substances listed below. The concentration of the individual substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in the NSF 42 & 53 standard.

Substance	Percent Reduction <small>(actual product performance)</small>	Influent Challenge <small>(mg/L unless specified)</small>	Max permissible water concentration <small>(mg/L unless specified)</small>
ALACHLOR ^①	>98%	0.050	0.001 ³
ASBESTOS ^②	>99.9%	fibers greater than 10 micrometers in length	99% reduction requirement
ATRAZINE ^①	>97%	0.100	0.003
BENZENE ^①	>99%	0.081	0.001
BROMODICHLOROMETHANE (TTHM) ^①	>99.8%	0.300 +/- 0.30	0.015
BROMOFORM (TTHM) ^①	>99.8%	0.300 +/- 0.30	0.015
CARBOFURAN (Furadan) ^①	>99%	0.190	0.001
CARBON TETRACHLORIDE ^①	98%	0.078	0.0018
CHLORAMINE as Aesthetic Effect (Monochloramine)	>99%	3.0 mg/L +/-10%	0.5mg/L
CHLORINE as Aesthetic Effect	>99%	2.0 mg/L +/-10%	> or = 50%
CHLOROBENZENE (Monochlorobenzene) ^①	>99%	0.077	0.001
CHLOROPICRIN ^①	99%	0.015	0.0002
CHLOROFORM (TTHM) ^① (surrogate chemical)	>99.8%	0.300 +/- 0.30	0.015
Cryptosporidium ^② (CYST)	99.95%	minimum 50,000/mL	99.95%
CYST ^② (Giardia; Cryptosporidium; Entamoeba; Toxoplasma)	99.95%	minimum 50,000/mL	99.95%
2, 4-D ^①	98%	0.110	0.0017
DBCP (see Dibromochloropropane) ^①	>99%	0.052	0.00002
1,2-DCA (see 1,2-DICHLOROETHANE) ^①	95%	0.088	0.0048
1,1-DCE (see 1,1-DICHLOROETHYLENE) ^①	>99%	0.083	0.001
DIBROMOCHLOROMETHANE (TTHM; Chlorodibromomethane) ^①	>99.8%	0.300 +/- 0.30	0.015
DIBROMOCHLOROPROPANE (DBCP) ^①	>99%	0.052	0.00002
o-DICHLOROBENZENE (1,2 Dichlorobenzene) ^①	>99%	0.080	0.001
p-DICHLOROBENZENE (para-Dichlorobenzene) ^①	>98%	0.040	0.001
1,2-DICHLOROETHANE (1,2-DCA) ^①	95%	0.088	0.0048
1,1-DICHLOROETHYLENE (1,1-DCE) ^①	>99%	0.083	0.001
CIS-1,2-DICHLOROETHYLENE ^①	>99%	0.170	0.0005
TRANS-1,2- DICHLOROETHYLENE ^①	>99%	0.086	0.001
1,2-DICHLOROPROPANE (Propylene Dichloride) ^①	>99%	0.080	0.001
CIS-1,3- DICHLOROPROPYLENE ^①	>99%	0.079	0.001
DINOSEB ^①	99%	0.170	0.0002
EDB (see ETHYLENE DIBROMIDE) ^①	>99%	0.044	0.00002
ENDRIN ^①	99%	0.053	0.00059
Entamoeba ^② (see CYSTS)	99.95%	minimum 50,000/mL	99.95%
ETHYLBENZENE ^①	>99%	0.088	0.001
ETHYLENE DIBROMIDE (EDB) ^①	>99%	0.044	0.00002
Furadan (see CARBOFURAN) ^①	>99%	0.190	0.001
Giardia Lamblia ^② (see CYST)	>99.95%	minimum 50,000/mL	99.95%

① Percent reduction reflects the allowable claims for Volatile Organic Chemicals/Compounds as per NSF/ANSI 53 Standard, Section 7.2.4.1.

② The carbon block in the Wellness Kitchen S-III is rated for 1 micron nominal filtration. Performance claim for Cysts based on NSF/ANSI 53 challenge protocol 7.3.2.2.4.3, which requires reduction of particles in the range of 3 +/- .15 micron. Performance claim for Asbestos based on NSF/ANSI 53 challenge protocol 7.3.1.4.3, which requires reduction of particles greater than 10 micron in length.



Wellness Enterprises, LLC
418 SW 140th Terrace
Newberry, FL 32669

Toll-free: 800-428-9419
Tel: 352-333-0480
Fax: 352-333-0490

Kitchen S-III Performance Data Sheet

Substance	Percent Reduction <small>(actual product performance)</small>	Influent Challenge <small>(mg/L unless specified)</small>	Max permissible water concentration <small>(mg/L unless specified)</small>
HALOACETONITRILES (HAN)^①			
BROMOCHLOROACETONITRILE	98%	0.022	0.0005
DIBROMOACETONITRILE	98%	0.024	0.0006
DICHLOROACETONITRILE	98%	0.0096	0.0002
TRICHLOROACETONITRILE	98%	0.015	0.0003
HALOKETONES (HK):^①			
1,1-DICHLORO-2-PROPANONE	99%	0.0072	0.0001
1,1,1-TRICHLORO-2-PROPANONE	96%	0.0082	0.0003
HEPTACHLOR ^①	>99%	0.25	0.00001
HEPTACHLOR EPOXIDE ^①	98%	0.0107	0.0002
HEXACHLOROBUTADIENE (Perchlorobutadiene) ^①	>98%	0.044	0.001
HEXACHLOROCYCLOPENTADIENE ^①	>99%	0.060	0.000002
LEAD (pH 6.5)	>99.3%	0.15 +/- 10%	0.010
LEAD (pH 8.5)	>99.3%	0.15 +/- 10%	0.010
LINDANE ^①	>99%	0.055	0.00001
METHOXYCHLOR ^①	>99%	0.050	0.0001
Methylbenzene (see TOLUENE) ^①	>99%	0.078	0.001
Monochlorobenzene (see CHLOROENZENE) ^①	>99%	0.077	0.001
PCE (see TETRACHLOROETHYLENE) ^①	>99%	0.081	0.001
PENTACHLOROPHENOL ^①	>99%	0.096	0.001
Perchlorobutadiene (see HEXACHLOROBUTADIENE) ^①	>98%	0.044	0.001
Propylene Dichloride (see 1,2 -DICHLOROPROPANE) ^①	>99%	0.080	0.001
SIMAZINE ^①	>97%	0.120	0.004
Silvex (see 2,4,5-TP) ^①	99%	0.270	0.0016
STYRENE (Vinylbenzene) ^①	>99%	0.150	0.0005
1,1,1-TCA (see 1,1,1 - TRICHLOROETHANE) ^①	95%	0.084	0.0046
TCE (see TRICHLOROETHYLENE) ^①	>99%	0.180	0.0010
1,1,2,2- TETRACHLOROETHANE ^①	>99%	0.081	0.001
TETRACHLOROETHYLENE ^①	>99%	0.081	0.001
TOLUENE (Methylbenzene) ^①	>99%	0.078	0.001
Toxoplasma ^② (see CYSTS)	99.95%	minimum 50,000/mL	99.95%
2,4,5-TP (Silvex) ^①	99%	0.270	0.0016
TRIBROMOACETIC ACID ^①	>98%	0.042	0.001
1,2,4 TRICHLOROENZENE (Unsymtrichlorobenzene) ^①	>99%	0.160	0.0005
1,1,1-TRICHLOROETHANE (1,1,1-TCA) ^①	95%	0.084	0.0046
1,1,2-TRICHLOROETHANE ^①	>99%	0.150	0.0005
TRICHLOROETHYLENE (TCE) ^①	>99%	0.180	0.0010
TRIHALOMETHANES ^① (TTHM) (Chloroform; Bromoform; Bromodichloromethane; Dibromochloromethane)	>95%	0.300 +/- 0.30	0.015
TRICHLOROENZENE ^①	>99%	0.160	0.0005
Vinylbenzene (see STYRENE) ^①	>99%	0.150	0.0005
XYLENES (TOTAL) ^①	>99%	0.070	0.001

① Percent reduction reflects the allowable claims for Volatile Organic Chemicals/Compounds as per NSF/ANSI 53 Standard, Section 7.2.4.1.

② The carbon block in the Wellness Kitchen S-III is rated for 1 micron nominal filtration. Performance claim for Cysts based on NSF/ANSI 53 challenge protocol 7.3.2.2.4.3, which requires reduction of particles in the range of 3 +/- .15 micron. Performance claim for Asbestos based on NSF/ANSI 53 challenge protocol 7.3.1.4.3, which requires reduction of particles greater than 10 micron in length.



Wellness Enterprises, LLC
 418 SW 140th Terrace
 Newberry, FL 32669

Toll-free: 800-428-9419
 Tel: 352-333-0480
 Fax: 352-333-0490

Kitchen S-III Performance Data Sheet

NOTES:

1. Chloroform was used as a surrogate for claims of reduction of VOCs. The Wellness Kitchen S-III tested at >99.8% actual reduction of Chloroform. Percent reduction shown herein reflects the allowable claims for VOCs as per tables in the Standard.
2. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
3. Filter life will vary in proportion to the amount of water used and the level of impurities in the water being processed. For optimum performance, it is essential that the filter be replaced on a regularly scheduled basis as follows: (a) annually; (b) when the unit's rated capacity has been reached; (c) the flow rate diminishes; (d) the filter becomes saturated with bad tastes and odors.
4. The Wellness Kitchen S-III includes a capacity monitor. The LCD automatically flashes and emits a beeping sound when it is time to replace your filter.
5. The Wellness Kitchen S-III is warranted as follows: All parts, workmanship and materials - 1 year. All exterior hoses and attachments are also warranted for one year. Please see the Owner's Manual for complete product guarantee and warranty information.
6. Please see the Owner's Manual for installation instructions and operating procedures.
7. In compliance with New York law, it is recommended that before purchasing a water treatment system, NY residents have their water supply tested to determine their actual water treatment needs. Please compare the capabilities of the Wellness Kitchen S-III with your actual water treatment needs.
8. Check for compliance with state and local laws and regulations.
9. While testing was performed under standard laboratory conditions, actual performance may vary.
10. The list of substances which the treatment device reduces does not necessarily mean that these substances are present in your tap water.



Wellness Kitchen S-III Product Technical Specifications	
Filtration & Enhancement media	Carbon block (coconut shell & proprietary mix), SPG Sand, Quartz, Magnetite, Bakuhan®, Tenko-Seki®, Taicho®, & High Gauss Magnets
Filtering flow rate	0.35 - 1.00 GPM (at 40 psi)
Maximum pressure (psi)	100 psi
Rated life	1,000 gallons/12 months
Operating temperatures	40°F. min - 100°F. max
Body dimensions	7.5" Wide x 5.5" Deep x 13.25" High Hose Length: 54"
Body weight (dry)	9 Pounds
Product Warranty	One year for workmanship & material defects